

M230i-S & SP

Safe and flexible labelling

The **M230i-S** and **M230i-SP** models provide a new level of safety to automated front or rear labelling without compromising performance operability. With an incorporated Autostop feature operator safety is ensured, whilst the compact footprint and flexible & rigid design makes them adaptable to your specific needs now and way into the future.



Performance

- ◆ Short version for maximum throughput and long version when reach is key.
- ◆ Articulated pad allows for label delivery to product panel variances.
- ◆ Label Check sensor ensures the label does not get lost.

Scan with camera
to watch it operate



Maximum uptime

- ◆ 600 m ribbon & label roll capacity within a compact footprint.
- ◆ Unique pad design allows for any label variation without changeover.
- ◆ Simple preventative maintenance access points.
- ◆ Easy to change long life thermal print heads.

Safer by design

- ◆ Innovative pinch point protection to prevent incidental contact injuries.
- ◆ Autostop feature to prevent damage in the event of an obstruction.
- ◆ Air loss detection and protection against system damage.





Two models to meet your needs

In order to be as flexible as possible two models, **M230i-S** and **M230i-SP** are available. Factors that determine which model to choose are:

- ◆ Desired throughput
- ◆ Label orientation
- ◆ Space availability
- ◆ Operator comfort and availability



Optional *TouchPanel* User Interface

For effortless control and status reporting *TouchPanel* is our unique, simplified operator interface that gets the printer into action quickly and simply. No complex menus or parameters, just enter the job and away you go.

- ◆ Quick access to favourite menus and settings via large user-friendly icons and customisable home screen.
- ◆ Easy prompted input of data into label templates.
- ◆ Speed up changeovers and help eliminate coding selection errors with simplified Message Store and live WYSIWYG preview.

Technical Specification

For labelling on the front or rear the **M230i-S** and **M230i-SP** can be configured to suit your specific needs. All M-Series units are equipped with a powerful Printer Control Unit (PCU).

		M230i-S4/SP4	M230i-S6/SP6
Print width		108 mm (4")	162 mm (6")
Print technology		Thermal Transfer / Direct Thermal	
Resolution		12 dots/mm (300dpi)	
Orientation		Left hand or Right hand	
Label & Ribbon lengths		Up to 600 m	
Typical capacity		55 labels/min	50 labels/min
Distance to product (to center of pad)		Up to 270 mm	
Label sizes (WxL)		25x15* mm - 150x210 mm *55 if Label Check required	
Dimensions (HxWxL)	S	Min: 625 x 262 x 735 mm Max: 625 x 262 x 941 mm	Min: 625 x 317 x 751 mm Max: 625 x 318 x 941 mm
	SP	Min: 625 x 379 x 619 mm Max: 625 x 489 x 681 mm	Min: 625 x 384 x 626 mm Max: 625 x 543 x 681 mm

		PCU
Communication		2xRS232, 1xUSB 2.0, Ethernet
I/Os (configurable)		10 Inputs and 10 Outputs
User interface		Graphical display with 25 languages
Dimensions (HxWxL)		130 x 280 x 405 mm

M230i-S4



M230i-SP4



CONTACT US

TALK TO AN EXPERT

+91-900 900 6612
 enquiry@dominoindia.com
 www.domino-printing.com



KNOW MORE

Domino Printech India LLP, 117, Sector - 8, IMT Manesar, Gurugram, Haryana, India - 122050

All performance related figures and claims quoted in this document were obtained under specific conditions and may only be replicated under similar conditions. For specific product details, you should contact your Domino Sales Advisor. This document does not form part of any terms and conditions between you and Domino. Images may include optional extras or upgrades. Print quality may differ depending on consumables, printer substrates and other factors. Images and photographs do not form any part of any terms and conditions between you and Domino.